

## ZoomGate Swing Door

Aesthetically simple, elegant and beautiful with brushed stainless steel finish, best suited for passage control of airports, hotels, art galleries and commercial buildings.

Passage width can be doubled to 1250mm to catered for passanger with luggages and easy access for the physically challenged.

Model: ZG-ASD-AR-01

### Safety:

Our modern motor mechanism will disengage when an object tries to block the flap from closing, providing an additional safety feature for the pedestrian.

### Detection Beams:

Radar Safety sensor detects object in door's swinging radius while opening to provide utmost protection for safety.



Wheelchair user friendly



# ZoomGate Flap Barrier

# Model: ZG - ASD - AR - 01

## Materials:

The cabinet panel are stainless steel. SUS304 as standard. Other options are available, SUS316 or mild steel powder coating with preferred colours.

## Housing:

The round and slim module enclosure suits most space conscious building interior. Door panel can be acrylic panel or glass limited to 600mm

## Specifications:

Input Voltage: 220V AC, 50Hz

Operating Voltage: 24V 100W

Dimension: 900(L) x 193(W) x 1020(H)

## Operation Mode:

Servo positioning drive opens and closes the door to the desired direction at low power. Remote controlled by an access control system or manually controlled. Opening time and angle are adjustable

## Features:

- Indicative LEDs on crown on gate's movement
- Open by push button or access control system
- Pre-programmed for automatic control
- Low Noise, high stability and reliable
- Encoder control rotating

